Janitorial Supplies - Exceptional Quality

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

J 121 - RED WINE STAIN REMOVER

Revision 3
Revision date 2015-05-29

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	RED WINE STAIN REMOVER

1.3. Details of the supplier of the safety data sheet

Company	EAGLE Distribution Ltd
Address	Broad Lane Cottenham CAMBS CB248SW
Web	www.eagleblue.co.uk
Telephone	+44 (0)1954 206500
Fax	-
Email	eagle.distribution.ltd@gmail.com
Email address of the competent person	

1.4. Emergency telephone number

Emergency telephone number	01530 272 922
Company	ASL (QUOTE EP03095)
24hrs	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/EC	Xi; R36 Symbols: Xi: Irritant.
Main hazards	Irritating to eyes.
2.1.2. Classification - EC 1272/2008	Eye Dam. 1: H318;

2.2. Label elements

Hazard pictograms	
Signal Word	Danger
Hazard Statement	Eye Dam. 1: H318 - Causes serious eye damage.
Precautionary Statement: Prevention	P102 - Keep out of reach of children. P103 - Read label before use. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P301+P310 - IF SWALLOWED: IF SWALLOWED: Immediately call a POISON CENTER/doctor/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

J 121 - RED WINE STAIN REMOVER

Revision 3
Revision date 2015-05-29

2.2. Label elements

	lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention.
Precautionary Statement: Disposal	P501 - Dispose of contents/container to rEQUIREMENTS OF LOCAL AUTHORITIES

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0	01-2119475108-36		Xn; R20/21/22 Xi; R36/38	
Sodium metabisulphite (Disodium disulphite)	016-063-00-2	7681-57-4	231-673-0			Xn; R22 Xi; R41 R31	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
WATER							
2 BUTOXY ETHANOL (2-Butoxyethanol)		111-76-2	203-905-0	01-2119475108-36		Acute Tox. 4: H302; Acute Tox. 4: H312; Skin Irrit. 2: H315; Eye Irrit. 2: H319; Acute Tox. 4: H332;	
Sodium metabisulphite (Disodium disulphite)	016-063-00-2	7681-57-4	231-673-0			Acute Tox. 4: H302; Eye Dam. 1: H318;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Irritating to respiratory system. Inhalation may cause coughing, tightness of the chest and irritation of the respiratory system. Move the exposed person to fresh air. Seek medical attention.
Eye contact	Irritating to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.
Skin contact	Irritating to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.
Ingestion	Ingestion may cause nausea and vomiting. Seek medical attention if irritation or symptoms persist. DO NOT INDUCE VOMITING.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Carbon dioxide (CO_2).

5.2. Special hazards arising from the substance or mixture

Burning produces irritating, toxic and obnoxious fumes.

5.3. Advice for firefighters

Wear suitable respiratory equipment when necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation of the working area. Wear suitable protective equipment.

6.2. Environmental precautions

Do not allow product to enter drains. Prevent further spillage if safe.

6.3. Methods and material for containment and cleaning up

Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for

6.3. Methods and material for containment and cleaning up

	disposal. Clean spillage area thoroughly with plenty of water.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.

7.2. Conditions for safe storage, including any incompatibilities

	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Exposure Limit Values

2 BUTOXY ETHANOL (2-Butoxyethanol)	WEL 8-hr limit ppm: 25 WEL 15 min limit ppm: 50 WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 123 WEL 15 min limit mg/m3: 101.2 WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -
Sodium metabisulphite (Disodium disulphite)	WEL 8-hr limit ppm: - WEL 15 min limit ppm: - WEL 8-hr limit mg/m3 total inhalable dust: - WEL 8-hr limit mg/m3 total respirable dust: -	WEL 8-hr limit mg/m3: 5 WEL 15 min limit mg/m3: - WEL 15 min limit mg/m3 total inhalable dust: - WEL 15 min limit mg/m3 total respirable dust: -

DNEL: Derived no-effect level.

Exposure Pattern - Workers

2 BUTOXY ETHANOL	Acute inhalation - Systemic effects 663 mg/m³ Acute inhalation - Local effects 246 mg/m³ Long-term - dermal - Systemic effects 75 mg/kg	Acute dermal - Systemic effects 89 mg/kg

Exposure Pattern - General population

2 BUTOXY ETHANOL	Acute inhalation - Systemic effects 426 mg/m³ Acute dermal - Systemic effects 44.5 mg/kg Long-term - inhalation - Local effects 123 mg/kg Long-term - oral - Systemic effects 3.2 mg/kg	Acute oral - Systemic effects 13.4 mg/kg Long-term - dermal - Systemic effects 38 mg/kg

8.2. Exposure controls

8.2.1. Appropriate engineering controls	Ensure adequate ventilation of the working area.
8.2.2. Individual protection measures	Wear chemical protective clothing.
Eye / face protection	Approved safety goggles.

J 121 - RED WINE STAIN REMOVER

Revision 3
Revision date 2015-05-29

8.2. Exposure controls

Skin protection - Hand protection	Chemical resistant gloves (PVC).
Respiratory protection	Wear:. Suitable respiratory equipment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Clear
Odour	Characteristic
pH	7.0 NOMINAL
Relative density	1.01 NOMINAL

Water solubility

	Soluble in water.

SECTION 10: Stability and reactivity

10.2. Chemical stability

	Stable under normal conditions.

10.3. Possibility of hazardous reactions

	Strong acids.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Skin corrosion/irritation	Irritating to eyes. Irritating to respiratory system.

SECTION 12: Ecological information

12.1. Toxicity

	No data is available on this product.

SECTION 13: Disposal considerations

General information

	Dispose of in compliance with all local and national regulations.

SECTION 14: Transport information

Further information

	The product is not classified as dangerous for carriage.

SECTION 15: Regulatory information

15.2. Chemical safety assessment

	No chemical Safety assessment has been carried out by the supplier.

SECTION 16: Other information

Other information

Revision	This document differs from the previous version in the following areas:. 2 - 2.1.2. Classification - EC 1272/2008. 2 - Hazard pictograms. 2 - Signal Word. 2 - Precautionary Statement: Prevention. 2 - Precautionary Statement: Response. 2 - Precautionary Statement: Disposal.

J 121 - RED WINE STAIN REMOVER

Revision 3
Revision date 2015-05-29

Other information

	12 - 12.1. Toxicity. 15 - 15.2. Chemical safety assessment.
Text of risk phrases in Section 3	R20/21/22 - Harmful by inhalation, in contact with skin and if swallowed. R22 - Harmful if swallowed. R31 - Contact with acids liberates toxic gas. R36/38 - Irritating to eyes and skin. R41 - Risk of serious damage to eyes.
Text of Hazard Statements in Section 3	Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation. EUH031 - Contact with acids liberates toxic gas. Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage.

Further information

	The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process.